



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : <b>B01F 3/08, 3/12, 3/18</b>	<b>A1</b>	(11) International Publication Number: <b>WO 00/37164</b>
		(43) International Publication Date: 29 June 2000 (29.06.00)
(21) International Application Number: PCT/SE99/02385	(81) Designated States: JP, NO, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 16 December 1999 (16.12.99)	<b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. In English translation (filed in Swedish).</i>	
(30) Priority Data: 9804442-3 21 December 1998 (21.12.98) SE		
(71) Applicant (for all designated States except US): GLOBAL POWDER AB [SE/SE]; Vesslövågen 13 A, S-183 40 Tåby (SE).		
(72) Inventor; and		
(75) Inventor/Applicant (for US only): ANDERSSON, Alf [SE/SE]; Box 23, S-269 35 Ödåkra (SE).		
(74) Agent: AWAPATENT AB; Box 5117, S-200 71 Malmö (SE).		

(54) Title: DEVICE AND METHOD FOR CONTINUOUS MIXING

## (57) Abstract

A device for continuous mixing of at least two components, such as liquids and/or powders. The device comprises a first means (8, 15) for joining the components in layers, and a second means (6, 18) for discharging the joined components during simultaneous deformation of a layer structure obtained in the joining, to provide a homogeneous mixture of components. The device is characterised in that the first means (8, 15) comprises a layering means (8) and a receiving means (15) rotatable about a longitudinal axis (13) and having a receiving surface (22) which faces the layering means (8) and is arranged radially outside the same. The layering means (8) is adapted to alternately dispose the components in the form of thin layers on the receiving surface (22) to form a stratum of layer structure, and the receiving means (15) is during rotation adapted to support said stratum. The present invention also relates to a method for continuous mixing of at least two components.

